



PCT/GB 2003 / 0 0 2 7 - 7 1



INVESTOR IN PEOPLE

#2

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

REC'D 0 8 AUG 2003

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed *AmBrewster*

Dated 29 July 2003

**CERTIFIED COPY OF  
PRIORITY DOCUMENT**

The  
Patent  
Office



The Patent Office  
Cardiff Road  
Newport  
Gwent NP9 1RH

**Request for grant of a patent**

See the notes on the back of this form. You can also get  
an explanatory leaflet from the Patent Office to help  
you fill in this form)

**1. Your reference**

MR/AC/37083

**0215063.9**

**2. Patent application**  
(The Patent Office will fill in this part)

01JUL02 E729659-2 002807  
P01/7700 0.00-0215063.9

28 JUN 2002

**3. Full name, address and postcode of the or of  
each applicant (underline all surnames)**

Alpha Thames Ltd  
Essex House  
Station Road  
Upminster, Essex  
RM14 2SU

**Patents ADP number (if you know it)**

**If the applicant is a corporate body, give the  
country/state of its incorporation**

United Kingdom

7581042001

**Title of the invention**

SYSTEM AND METHOD FOR THE REMOVAL OF  
PARTICULATES FROM WATER

**Name of your agent (if you have one)**  
**"Address for service" in the United Kingdom**  
**to which all correspondence should be sent**  
(including the postcode)

BARON & WARREN  
18 SOUTH END  
KENSINGTON  
LONDON  
W8 5BU

**Patents ADP number (if you know it)**

281001

**If you are declaring priority from one or more  
earlier patent applications, give the country  
and the date of filing of the or of each of these  
earlier applications and (if you know it)**

Country

Priority application number  
(if you know it)

Date of filing  
(day/month/year)

**If this application is divided or otherwise  
derived from an earlier UK application,  
give the number and the filing date of  
the earlier application**

Number of earlier application

Date of filing  
(day/month/year)

**Is a statement of inventorship and of right  
to grant of a patent required in support of  
this request (Answer 'Yes' if:**

YES

- a) any applicant names in part 3 is not an inventor, or
- b) there is an inventor who is not named as an  
applicant, or
- c) any names applicant is a corporate body.

BEST AVAILABLE COPY  
BEST AVAILABLE COPY

Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form

Description

Claim(s)

Abstract

Drawing(s)

7

4 x 4 5

1. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

BEST AVAILABLE COPY

1. I/We request the grant of a patent on the basis of this application.

Signature

Date 28 June 2002

*Baron & Warren*

BARON & WARREN  
Agents for the Applicant

2. Name and daytime telephone number of person to contact in the United Kingdom

Michael Robinson 020 7937 0294

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- 1) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- 2) Write your answers in capital letters using black ink or you may type them.
- 3) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- 4) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- 5) Once you have filled in the form you must remember to sign and date it.

For details of the fee and ways to pay please contact the Patent Office.

SYSTEM AND METHOD FOR THE REMOVAL OF PARTICULATES FROM  
WATER

5 The present invention relates to the removal of particulates from water, particularly in situations when seawater is to be used for injection into a hydrocarbon reservoir.

10 In an oil and/or gas field development, production fluid, extracted from the hydrocarbon reservoir via production wells, is normally driven to a host facility by the natural pressure of the reservoir. However, the natural pressure varies from field to field and some reservoirs, particularly in later field life, may not have enough natural pressure to drive the production fluid to the host facility.

15 A way of overcoming this problem is to boost the pressure of the reservoir by injecting seawater, via water injection wells, into the reservoir at a pressure higher than the pressure of the fluid in the reservoir. Where this has been done previously, seawater is pumped from the sea up to a host facility such as a floating platform where it is treated so as to make it suitable for injection into the hydrocarbon reservoir. Such treatment may include both the use of chemicals and  
20 particulate removal in a settlement tank to allow suspended sediment to settle and be separated from the seawater. If such sediment is not removed it will cause abrasive wear in equipment and pipelines that the seawater passes through and may adversely affect production from the hydrocarbon reservoir. The substantially sediment free seawater is then pumped from the settlement tank at high pressure  
25 down to the water injection wells and into the reservoir.

Pipelines are required to convey the treated water from the host facility to the injection wells and these pipelines have to have a pipe wall thick enough to withstand the high internal pressure of the treated seawater. The capital costs  
30 of such pipelines and the installation costs are high.

Thus, the process for injecting seawater into injection wells, requires seawater to be pumped up to a host facility where it is suitably treated before being pumped at high pressure into the wells. This process involves expensive equipment such as high pressure pipelines and pumps. Furthermore, the large amount of energy required to pump the seawater over a long distance from the host facility to the injection wells will increase the running costs.

An object of the invention is to overcome at least some of the problems referred to above.

Thus, according to one aspect of the present invention there is provided a system for use underwater for removing particulates from water, comprising dynamic separating means for removing particulates from water, and pumping means downstream from the dynamic separating means for drawing water upstream of the separating means into the separating means.

The pumping means may be used to inject at least substantially particulate free water from the dynamic separating means into a hydrocarbon reservoir at a pressure higher than the pressure of the fluid in the reservoir.

By providing such a system underwater, the length of high pressure pipelines required between the pumping means and injection wells can be much less than when treated seawater is to be pumped from a host facility. A pump is not required upstream of the separating means to pump water into the separating means (as in the prior art arrangement explained above) and the abrasion problem associated with pumping particulate laden seawater is thereby avoided.

The dynamic separating means may comprise at least one dynamic

separator. Such separators are simple, compact, self-contained units which are suitable for use underwater. The dynamic separating means may comprise one or more hydrocyclones.

5           The system may be provided with means for collecting particulates separated from said water by the dynamic separating means and means for removing collected particulates from the particulate collecting means. The particulate removal means may continuously remove collected particulates or periodically remove collected particulates. Preferably, the system includes  
10 means for directing at least some of the at least substantially particulate free water from the dynamic separating means to the particulate removal means to enable the particulate removal means to remove collected particulates. The particulate removal means may comprise a venturi flume.

15           The system may have a filter upstream of the dynamic separating means for preventing large items such as fish from entering the separating means.

          Preferably, the system is incorporated into a retrievable module for use with a modular seabed processing system.

20

          According to another aspect of the present invention there is provided an underwater method for removing particulates from water, comprising the steps of pumping water downstream of dynamic separating means to draw water upstream of the separating means into the separating means, and separating  
25 particulates from the water in the dynamic separating means.

          The method preferably includes the subsequent step of injecting at least substantially particulate free water from the dynamic separating means into a hydrocarbon reservoir at a pressure higher than the pressure of the fluid in the  
30 reservoir.

The invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 schematically shows a system in accordance with an embodiment of the present invention;

Figure 2 is a schematic detail of the inside of a module for the system of Figure 1;

Figure 3 is a modification of Figure 2; and

Figure 4 is a modification of Figure 3.

10

Referring to Figures 1 and 2 of the accompanying drawings, the system 1 is accommodated in a retrievable module 2 which is connected to a base structure 3 on a seabed by a multi-ported fluid connector 4 for enabling isolation of the module 2 from the base structure 3. The module 2 may be of the general type forming part of a modular system for subsea use designed by Alpha Thames Limited of Essex, United Kingdom, and referred to as AlphaPRIME.

The module 2 contains a sand or particulate or particle removal device 5, a sand storage vessel 6, a dynamic sand extraction device 7, and a pump 8. The sand removal device 5 is a dynamic separator and may be a hydrocyclone separator of the type produced by Axsia Mozley of Redruth, Cornwall, United Kingdom. The sand removal device 5 has a fluid inlet 9, a fluid outlet 10 and a sand or particle outlet 11. The fluid inlet 9 is connected via a fluid inlet conduit 12 to a coarse filter 13 located on an outside face of the module 2, and the fluid outlet 10 is connected to the multi-ported fluid connector 4 by a fluid outlet conduit 14 containing the pump 8. The fluid outlet conduit 14 is connected to a conduit 15 leading to one or more water injection wells (indicated by arrow 16) via the multi-ported fluid connector 4 and each conduit 14,15 includes an isolation valve 17 on either side of the fluid connector 4.

30

The sand outlet 11 of the sand removal device 5 is connected to a sand inlet 18 of the sand storage vessel 6 below via an actuable isolation valve 19. The vessel 6 has a sand outlet 20 which is connected to the sand extraction device 7 below by a flange connection 21.

5

The dynamic sand extraction device 7 is connected by a bypass conduit 22 to the fluid outlet conduit 14 downstream of the pump 8 and the bypass conduit 22 has a flow and pressure restriction device 23 and an actuable isolation valve 24 downstream of the device 23. The bypass conduit 22 is connected to a side 25 of the sand extraction device 7 and a sand removal conduit 26 extends through the base 27 of the device 7 and up into the lower portion 28 of the sand storage vessel 6 via the flange connection 21. The sand removal conduit 26 extends in the opposite direction to connect to a port 29 on the side of the module 2, and has an actuable isolation valve 30 between the sand extraction device 7 and the port 29.

15

The operation of the system 1 will now be described.

The isolation valve 19 between the sand removal device 5 and the sand storage device 6 is set to be open and the isolation valves 24,30 on either side of the sand extraction device 7 are set to be closed. The pump 8 in the module 2 is activated to draw raw seawater into the sand removal device 5 via the coarse filter 13. The flow induced by the pump 8 results in a helical flow being established in the device 5 which leads to the separation of sand and other particulates from the seawater. The sand removal device 5 removes sand and other particulates from the seawater, and the separated sand is collected in the lower portion of the sand storage device 6 therebelow. The pump 8 pumps the seawater separated from the sand via the fluid outlet 10 and the multi-ported fluid connector 4 into the water injection well(s).

30



Periodically, the sand storage device 6 is flushed. The isolation valve 19 between the sand removal device 5 and the sand storage device 6 is closed and the isolation valves 24,30 on either side of the sand extraction device 7 are opened. A portion of the seawater in the fluid outlet conduit 14 is carried by the bypass conduit 22 into the sand extraction device 7 which causes it to swirl into the lower portion of the sand storage device 6 and flush collected sand into the sand removal conduit 26 and out into the surrounding sea via the port 29.

Figure 3 illustrates a modification of the system 1 whereby the sand removal device 5 and the sand storage device 6 are replaced by a combined sand removal and storage device 31.

In Figure 4, the sand removal and storage device 31 is connected to an ejector 32 instead of a sand extraction device 7, and the isolation valves 24,30, which were either side of the sand extraction device 7, are removed. The ejector 32 is a venturi flume and the bypass conduit 22 is connected to the inlet end of it and an outlet conduit 33 connects the other end of it to the module port (not shown). The waist of the venturi flume 32 is connected to the sand outlet 34 of the sand removal and storage device 31 by a sand outlet conduit 35.

The modified system of Figure 4 is designed to flush sand continuously from the sand removal and storage device 6. Flow of seawater from the bypass conduit 22 through the ejector 32 draws sand down from the sand removal and storage device 6 and the sand and seawater are ejected into the surrounding sea via the port 29.

Whilst embodiments have been described, it will be understood that various modifications may be made without departing from the scope of the invention. For example, for any of the above arrangements the conduit 26,33 to the port 29 may have a one-way valve to prevent seawater surrounding the module 2 from being

sucked into the module 2:

The arrangement for removing collected sand illustrated in Figure 3 may be designed to continuously take separated sand away by removing the isolation  
5 valves 24,30 on either side of the sand extraction device 7.

For the above described embodiments, the multi-ported fluid connector 4 may be replaced by a fluid connector with a single bore.




Fig 1

Fig 2




Fig 3




Fig 4

